



VGRCB-15CPF / VGFCB-15CPF

The VGRCB-15CPF provides 15 contacts for coax, power or a combination of both contact styles. Coax contacts are provided for signals up to 500Mhz and power signals up to 30 Amps / 250 VAC. Proper alignment is ensured by two precision alignment pins per block. Two shoulder mounting screws per VGR block allow the block to float in the receiver. Contacts, blocks and cables sold separately.



Coax Contact Pair Specifications

Voltage	250VAC
Current	1.5 Amps
Contact Resistance	6mΩ
Capacitance	5pf
Inductance	3nH
Bandwidth	500Mhz
Durability	25,000 Cycles
Coax Connection Type	Crimp

Power Contact Pair Specifications

Power Contact	30 Amps
---------------	---------

Ordering Information:

Receiver Module:	VGRCB-15CPF Ref No (910)	Fixture Module:	VGFCB-15CPF Ref No (911)
36" Receiver Coax Cable Assy.	CR-CA50RG174-36	36" Fixture Coax Cable Assy.	CF-CA50RG174-36
Receiver Power Contact	CR-610116102	10 AWG Fixture Power Contact	CF-610115102
		12 AWG Fixture Power Contact	CF-610115-103

Accessories

Receiver Contact Extraction Tool	VGRXT	Fixture Contact Extract Tool	VGFXT
Receiver Alignment Pin Installation Tool	B32503		

For more information about VG Mass Interconnect products:
Contact your Local Sales Representative at www.ect-cpg.com/principal-offices
Visit ECT Online at www.ect-cpg.com/vg-mass-interconnect-products



A Cohu Company